

## INFOPRINT 75 AND INFOPRINT 100 LASER CONTINUOUS FORMS PRINTERS

### HIGHLIGHTS

- Production speeds up to 154 IPM.<sup>1</sup>
- High quality 600 DPI output.
- Easy to use auto-loading pin-feed paper path.
- Standard internal powered output stacker.
- Small footprint (under 9 square feet or .8 square meters).
- Supports common printer data languages PostScript® 3™ and PCL.
- IPDS is now available.
- Broad range of service offerings including 7x24 coverage.



InfoPrint 75 and InfoPrint 100 are new laser printers that provide the document sequence integrity of continuous forms printing in a compact footprint backed by around-the-clock service. For documents that must remain in page sequence, the InfoPrint 75 or InfoPrint 100 can print invoices, picking slips, labels or mailings with the high throughput of a continuous forms printer. These entry-level continuous forms printers feature ease of loading for box fanfold forms and easy unloading from a power stacker. The highly reliable tractor feed paper path can print forms formatted in

1-up landscape format or 2-up portrait format with a simple adjustment in the paper path. The print speeds range from 75 impressions per minute up to 154 impressions per minute,<sup>1</sup> providing very efficient operation. Print output is at 600 DPI, providing superb clarity on text, graphics and sharply defined barcodes. The InfoPrint 75 and InfoPrint 100 are backed by InfoPrint Availability Services that can be tailored to your operating requirements. These printers support an energy-efficient operation.

## INFOPRINT 75 AND INFOPRINT 100 CONTINUOUS FORMS PRINTERS

Item	Specifications	
<b>Print speed<sup>1</sup></b>	<b>InfoPrint 75</b>	<b>InfoPrint 100</b>
Linear feet/per minute	53.25	71
Linear meters/per minute	16.23	21.64
1-up Letter – Landscape	75 ipm	100 ipm
2-up 8.5" x 11"	116 ipm	154 ipm
1-up A4 Landscape	77 ipm	103 ipm
2-up A4	109 ipm	145 ipm
<b>Media</b>	<b>InfoPrint 75 and InfoPrint 100</b>	
Paper width	6.5" to 18" (165 mm to 457 mm)	
Paper weight	17 lb. to 42 lb. (64 gsm to 157 gsm)	
Paper length	6" to 14" (152 mm to 356 mm)	
Paper types	Continuous tractor forms, tip-on cards and labels	
<b>System attachments</b>	Ethernet (10Base-T/100Base-TX/1000Base-T automatic switching), TCP/IP (lpr, RawTCP), EtherTalk	
<b>Software support</b>	<p>PostScript 3 (Optional) and PCL5e (Standard): InfoPrint Manager for AIX® V4.3 PSU1 (PSF command and passthrough printer types only), InfoPrint Manager for Windows® V2.3 PSU1 (PSF command and passthrough printer types only), InfoPrint ProcessDirector V1.2.1 (passthrough printer type only)</p> <p>IPDS (Optional): PSF for Z/OS V4R1 or above, PSF/400 V5R3 or later, InfoPrint Manager for AIX V4.3 PSU1, InfoPrint Manager for Windows V2.3 PSU1, InfoPrint ProcessDirector for Linux® V1.3.1 Service Pack 2, InfoPrint ProcessDirector for AIX V1.3.1 Service Pack 2</p>	
<b>Standard features</b>	<p>Resolution: 600 DPI, 512 MB memory</p> <p>Power Stacker: 2,000 sheets at 17 lb./64 gsm</p>	

---

## INFOPRINT 75 AND INFOPRINT 100 CONTINUOUS FORMS PRINTERS

---

### Print Imaging Area characteristics (per engine)

Maximum Image Size (width) 17"

### Dimensions and Weight

Length	35" (890 mm)
Depth	36/39" (905/985 mm)
Height	55" (1,383 mm)
Weight	792 lb. (360 kg)

### Power requirements

200/240 V ac/50 Hz or 60 Hz single phase, 2 wires and grounding wire  
Voltage determined by country standards

### Environmental conditions

Permitted ranges	Temperature: 61° to 89°F (16° to 32°C) Relative humidity: 20% to 80% RH
Optimal ranges	Temperature: 66° to 77°F (19° to 25°C) Relative humidity: 30% to 65% RH
Acoustics	65 dBA (operating) or 50 dBA (idle)
Altitude	0 - 7,000 feet (0 - 2100 meters)

---

**FOR MORE INFORMATION**

Contact your InfoPrint Solutions Company representative or InfoPrint Solutions Partner or visit:

[Infoprint.com](http://Infoprint.com)

© Copyright InfoPrint Solutions Company 2009.  
All rights reserved.

InfoPrint Solutions Company  
6300 Diagonal Highway 002J  
Boulder, Colorado 80301-9270  
U.S.A.

Printed in the United States of America  
June 2009

Ricoh and the Ricoh logo are registered trademarks of Ricoh Co., Ltd. in Japan, other countries or both. IBM and the IBM logo are registered trademarks of International Business Machines Corporation in the United States, other countries, or both. The Ricoh and IBM trademarks are used under license from their respective trademark owners.

InfoPrint Solutions Company is a trademark of InfoPrint Solutions Company, LLC, in the United States, other countries, or both. InfoPrint is a registered trademark of Ricoh Co., Ltd., in the United States, other countries, or both. InfoPrint is used under license from the trademark owner.

References in this publication to InfoPrint Solutions Company products or services do not imply that InfoPrint Solutions Company intends to make them available in all countries in which InfoPrint Solutions Company operates. Any purchase of such products or services will be exclusively governed by the terms of the sales or license agreement applicable to such purchase to the maximum extent allowed by law.

These terms are trademarks or registered trademarks of Ricoh Co., Ltd., in the United States, other countries, or both: InfoPrint, IPDS and Ricoh.

These terms are trademarks or registered trademarks of International Business Machines Corporation in the United States, other countries, or both: IBM, AIX and the IBM logo.

Linux is a registered trademark of Linus Torvalds in the United States, other countries, or both.

PostScript and PostScript 3 are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States and/or other countries.

Windows is a trademark of Microsoft Corporation in the United States, other countries, or both.

Other company, product, or service names may be trademarks or service marks of others.

<sup>1</sup> Exact speed varies depending on document complexity, system configuration, software application, driver, and printer state.